

● YOUR
● SMART
● ENERGY



SMILE5

RESIDENTIAL SERIES

CAPACITY ▶

2.9 / 5.7 / 10.1 / 13.3 kWh modular
expandable to 80.0 kWh



5kW single phase hybrid inverter

Fast response

UPS ability

24/7 Monitoring

- S**elf sufficient
- M**odular battery
- I**ntelligent control
- L**ong lifespan
- E**ssential load protected
- 5** kW system

SMILE5



Model		SMILE5			
System Specification					
Nominal Output Power		5000 W / 4600 W (DE)			
Capacity Range	2.9 ~ 17.2 kWh (96% DoD)	5.7 ~ 34.4 kWh (96% DoD)	10.1 ~ 60.6 kWh (90% DoD)	13.3 ~ 80.0 kWh (100% DoD)	
Usable Capacity Range	2.8 ~ 16.5 kWh	5.5 ~ 33.0 kWh	9.1 ~ 54.4 kWh	13.3 ~ 80.0 kWh	
Battery Chemistry		LFP (LiFePO4)			
IP Protection		IP21 (Indoor) / IP65 (Outdoor)			
Warranty		5 Year Product Warranty, 10 Year Battery Warranty			

Inverter Technical Specification			
Model	SMILE5-INV	Rated Frequency	50 / 60 Hz
Max. PV Input Power	2 x 3300 W	Phase	Single-Phase
Max. PV Input Current	2 x 12 A	Backup	UPS
Max. PV Input Voltage	580 V	Display	LCD
MPPT Number	2	Communication	Ethernet
MPPT Voltage Range	125 ~ 550 V	Start Up DC Voltage	125 V
Max. PV Short-circuit Current	2 x 15 A	Humidity	15% ~ 85% (No Condensing)
Max. Charging/Discharging Current	100 A	Dimension (W x D x H)	610 x 236 x 615 mm
Max. Charging/Discharging Power	5000 W	Weight	60 kg
Rated Voltage	230 V	Safety	IEC 62109-1&-2, IEC 62477-1, IEC 62040.1.1, IEC 62116
Grid Voltage Range	180 ~ 270 V	EMC	EN 61000-6-1/2/3/4
Grid Regulation	VDE-AR-N 4105, VDE 0126-1-1, AS 4777.2/3, CEI 0-21, G99-1, G100, RD 1699, NRS 097-2-1, TOR D4		

Battery Technical Specification				
Module Model	M4856-P	SMILE5-BAT	SMILE-BAT-10.1P	SMILE-BAT-13.3P
Module Capacity	2.9 kWh	5.7 kWh	10.1 kWh	13.3 kWh
Module Nominal Voltage	51.2 V	51.2 V	48 V	48 V
Operating Temperature Range	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*
Max. Modules in Parallel	6	6	6	6**
Max. Charging/Discharging Current	56 A (1C)	56 A (0.5C)	100 A (0.5C)	100A (0.35C)
Cycle Life	10 000***	10 000***	8000	8000

* When the temperature is below 0 °C or above 40 °C, the performance will be limited.

** ≥2 needs to install expansion pack

*** Under specific test conditions



Headquarter: Alpha ESS Co., Ltd.

+86 513 8060 6891
 info@alpha-ess.com
 www.alpha-ess.com
 Jihua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609
 info@alpha-ess.com
 www.alpha-ess.com
 Level 15, SIP 158 Wangdun Road SIP Suzhou, 215028

Australia: Alpha ESS Australia Pty. Ltd.

+61 402 500 520 (Sales)
 +61 1300 968 933 (Technical Support)
 australia@alpha-ess.com
 www.alpha-ess.com.au
 Suite 1, Level 1, 530 Botany Road, Alexandria, NSW, 2015

Germany: Alpha ESS Europe GmbH

+49 6103 4591 601
 europe@alpha-ess.de
 www.alpha-ess.de
 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Italy: Alpha ESS Italy S.r.l.

+39 599 239 50
 info@alpha-ess.it
 www.alpha-ess.it
 Via Loda, 17-41013 Castelfranco Emilia (MO)

Korea: Alpha ESS Korea Co., Ltd.

+82 64 721 2004
 korea@alpha-ess.com
 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

UK: Alpha ESS UK Ltd.

uk@alpha-ess.com
 Drake House, Long Street, Dursley, gl11 4hh